

(19)



JAPANESE PATENT OFFICE

## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **08247301 A**

(43) Date of publication of application: **27.09.1996**

(51) Int. Cl **F16K 1/36**

**F16K 1/42, F16K 7/17, F16K 31/128**

(21) Application number: **08028154**

(22) Date of filing: **15.02.1996**

(30) Priority: **15.02.1995 CH 95 439**

(71) Applicant: **GEORG FISCHER  
ROHRLEITUNGSSYST AG**

(72) Inventor: **SCHALK ADELBERT  
GREITMANN RALF**

(54) **VALVE**

and tight sealing in a valve can be secured by a ring-shaped sealing face 58 based on the diaphragm 36.

(57) Abstract:

**PROBLEM TO BE SOLVED:** To provide a valve having a movable face making no direct contact with a flow medium so as to secure a maximum valve operation efficiency even when using an irritable medium.

**SOLUTION:** In a channel 16 of a housing 10, a diaphragm 36 seals a cylindrical chamber 48 from a medium inside the channel 16, while a disc 44 arranged in one end of a sleeve 40 divides the cylindrical chamber 48 into small chambers 50, 52. According to a shift of the sleeve 40, the other end face 42 is forcibly pressed to a guiding face 34 in a flow main body 18,

COPYRIGHT: (C)1996,JPO

